

0.1 poisson: Poisson Regression for Event Count Dependent Variables

Use the Poisson regression model if the observations of your dependent variable represents the number of independent events that occur during a fixed period of time (see the negative binomial model, Section ??, for over-dispersed event counts.) For a Bayesian implementation of this model, see Section ??.

Syntax

```
> z.out <- zelig(Y ~ X1 + X2, model = "poisson", data = mydata)
> x.out <- setx(z.out)
> s.out <- sim(z.out, x = x.out)
```

Additional Inputs

In addition to the standard inputs, `zelig()` takes the following additional options for poisson regression:

- **robust**: defaults to FALSE. If TRUE is selected, `zelig()` computes robust standard errors via the `sandwich` package (see Zeileis (2004)). The default type of robust standard error is heteroskedastic and autocorrelation consistent (HAC), and assumes that observations are ordered by time index.

In addition, `robust` may be a list with the following options:

- **method**: Choose from
 - * "vcovHAC": (default if `robust` = TRUE) HAC standard errors.
 - * "kernHAC": HAC standard errors using the weights given in Andrews (1991).
 - * "weave": HAC standard errors using the weights given in Lumley and Heagerty (1999).
- **order.by**: defaults to NULL (the observations are chronologically ordered as in the original data). Optionally, you may specify a vector of weights (either as `order.by` = `z`, where `z` exists outside the data frame; or as `order.by` = `~z`, where `z` is a variable in the data frame). The observations are chronologically ordered by the size of `z`.
- ...: additional options passed to the functions specified in `method`. See the `sandwich` library and Zeileis (2004) for more options.

Example

Load sample data:

```
> data(sanction)
```

Estimate Poisson model:



```
> z.out <- zelig(num ~ target + coop, model = "poisson", data = sanction)  
> summary(z.out)
```

Set values for the explanatory variables to their default mean values:

```
> x.out <- setx(z.out)
```

Simulate fitted values:

```
> s.out <- sim(z.out, x = x.out)  
> summary(s.out)  
> plot(s.out)
```



Model

Let Y_i be the number of independent events that occur during a fixed time period. This variable can take any non-negative integer.

- The Poisson distribution has *stochastic component*

$$Y_i \sim \text{Poisson}(\lambda_i),$$

where λ_i is the mean and variance parameter.

- The *systematic component* is

$$\lambda_i = \exp(x_i\beta),$$

where x_i is the vector of explanatory variables, and β is the vector of coefficients.

Quantities of Interest

- The expected value (`qi$ev`) is the mean of simulations from the stochastic component,

$$E(Y) = \lambda_i = \exp(x_i\beta),$$

given draws of β from its sampling distribution.

- The predicted value (`qi$pr`) is a random draw from the poisson distribution defined by mean λ_i .
- The first difference in the expected values (`qi$fd`) is given by:

$$\text{FD} = E(Y|x_1) - E(Y | x)$$

- In conditional prediction models, the average expected treatment effect (`att.ev`) for the treatment group is

$$\frac{1}{\sum_{i=1}^n t_i} \sum_{i:t_i=1}^n \{Y_i(t_i = 1) - E[Y_i(t_i = 0)]\},$$

where t_i is a binary explanatory variable defining the treatment ($t_i = 1$) and control ($t_i = 0$) groups. Variation in the simulations are due to uncertainty in simulating $E[Y_i(t_i = 0)]$, the counterfactual expected value of Y_i for observations in the treatment group, under the assumption that everything stays the same except that the treatment indicator is switched to $t_i = 0$.

- In conditional prediction models, the average predicted treatment effect (`att.pr`) for the treatment group is

$$\frac{1}{\sum_{i=1}^n t_i} \sum_{i:t_i=1}^n \left\{ Y_i(t_i = 1) - \widehat{Y_i(t_i = 0)} \right\},$$

where t_i is a binary explanatory variable defining the treatment ($t_i = 1$) and control ($t_i = 0$) groups. Variation in the simulations are due to uncertainty in simulating $\widehat{Y_i(t_i = 0)}$, the counterfactual predicted value of Y_i for observations in the treatment group, under the assumption that everything stays the same except that the treatment indicator is switched to $t_i = 0$.

Output Values

The output of each Zelig command contains useful information which you may view. For example, if you run `z.out <- zelig(y ~ x, model = "poisson", data)`, then you may examine the available information in `z.out` by using `names(z.out)`, see the `coefficients` by using `z.out$coefficients`, and a default summary of information through `summary(z.out)`. Other elements available through the `$` operator are listed below.

- From the `zelig()` output object `z.out`, you may extract:
 - `coefficients`: parameter estimates for the explanatory variables.
 - `residuals`: the working residuals in the final iteration of the IWLS fit.
 - `fitted.values`: a vector of the fitted values for the systemic component λ .
 - `linear.predictors`: a vector of $x_i\beta$.
 - `aic`: Akaike's Information Criterion (minus twice the maximized log-likelihood plus twice the number of coefficients).
 - `df.residual`: the residual degrees of freedom.
 - `df.null`: the residual degrees of freedom for the null model.
 - `zelig.data`: the input data frame if `save.data = TRUE`.
- From `summary(z.out)`, you may extract:
 - `coefficients`: the parameter estimates with their associated standard errors, *p*-values, and *t*-statistics.
 - `cov.scaled`: a $k \times k$ matrix of scaled covariances.
 - `cov.unscaled`: a $k \times k$ matrix of unscaled covariances.
- From the `sim()` output object `s.out`, you may extract quantities of interest arranged as matrices indexed by simulation \times `x`-observation (for more than one `x`-observation). Available quantities are:
 - `qi$ev`: the simulated expected values given the specified values of `x`.
 - `qi$pr`: the simulated predicted values drawn from the distributions defined by λ_i .
 - `qi$fd`: the simulated first differences in the expected values given the specified values of `x` and `x1`.

- `qi$att.ev`: the simulated average expected treatment effect for the treated from conditional prediction models.
- `qi$att.pr`: the simulated average predicted treatment effect for the treated from conditional prediction models.

How to Cite

To cite the *poisson* Zelig model:

Kosuke Imai, Gary King, and Olivia Lau. 2007. “*poisson*: Poisson Regression for Event Count Dependent Variables,” in Kosuke Imai, Gary King, and Olivia Lau, “Zelig: Everyone’s Statistical Software,” <http://gking.harvard.edu/zelig>.

To cite Zelig as a whole, please reference these two sources:

Kosuke Imai, Gary King, and Olivia Lau. 2007. “Zelig: Everyone’s Statistical Software,” <http://GKing.harvard.edu/zelig>.

Kosuke Imai, Gary King, and Olivia Lau. 2008. “Toward A Common Framework for Statistical Analysis and Development,” *Journal of Computational and Graphical Statistics*, forthcoming, <http://gking.harvard.edu/files/abs/z-abs.shtml>.

See also

The *poisson* model is part of the `stats` package by Venables and Ripley (2002). Advanced users may wish to refer to `help(glm)` and `help(family)`, as well as McCullagh and Nelder (1989). Robust standard errors are implemented via the `sandwich` package by Zeileis (2004). Sample data are from Martin (1992).

Bibliography

- Andrews, D. W. (1991), “Heteroskedasticity and Autocorrelation Consistent Covariance Matrix Estimation,” *Econometrica*, 59, 817–858.
- Lumley, T. and Heagerty, P. (1999), “Weighted Empirical Adaptive Variance Estimators for Correlated Data Regression,” *jrssb*, 61, 459–477.
- Martin, L. (1992), *Coercive Cooperation: Explaining Multilateral Economic Sanctions*, Princeton University Press, please inquire with Lisa Martin before publishing results from these data, as this dataset includes errors that have since been corrected.
- McCullagh, P. and Nelder, J. A. (1989), *Generalized Linear Models*, no. 37 in Monograph on Statistics and Applied Probability, Chapman & Hall, 2nd ed.
- Venables, W. N. and Ripley, B. D. (2002), *Modern Applied Statistics with S*, Springer-Verlag, 4th ed.
- Zeileis, A. (2004), “Econometric Computing with HC and HAC Covariance Matrix Estimators,” *Journal of Statistical Software*, 11, 1–17.